












Katalog opreme za kontrolu pristupa - CDVI - 23.07.2019.










KOMUNIKACIONI MODULI

| | | | |
|---|--|--------|---|
|  CDVI Konverter USB na RS-485 Konvertuje RS-485 protokol na USB ili RS-232 protokol, komunikacija sa CT-V900-A kontrolerom do 1220m. | CA-A360-USBR5 96.25 | 77.00 |  |
|  CDVI Četvoroportni RS-485 mrežni hub Dozvoljava implementaciju konfiguracija zvezde na velikim ili distribuiranim objektima. Radi na 12V i obezbeđuje jedan mrežni ulaz i 4 nezavisna izlazna porta. Šest LED dioda prikazuju status napajanja ili mrežnu aktivnost. *Opciona metalna kutija 20cmx25cmx8cm |  CA-A370-P 241.25 | 193.00 |  |

DODATNI MODULI

| | | | |
|---|----------------------------|--------|--|
|  CDVI LCD modul za praćenje Komunicira sa delom softvera koji je zadužen za kontrolu radnog vremena putem CT-V900-A E-BUS konekcije. Prikazuje vreme, broj kartice i/ili status kartice. Povezivanje do 8 tastatura na jedan CT-V900-A kontroler. | CK-TRAK-L 200.00 | 160.00 |  |
|  CDVI Dead bolt monitoring jedinica | CPDT 30.00 | 24.00 |  |

SISTEMSKI SOFTVER CENTAUR

| | | | |
|---|---|---------|---|
|  CDVI Centaur 6 - Standard Edition Podržava do 64 sistema, 32 kontrolera*, 128 vrata* i 2048 kartica*, podržava kontrolisanje liftova, podržava integraciju sa sistemima video nadzora, komunicira sa kontrolerima lokalno (RS-232/RS-485) ili udaljeno (korišćenjem IP modula CA-ETHR-A), aktivira se korišćenjem hardverskog USB ključa <i>* Broj kontrolera, vrata i kartica je izražen po pojedinačnom sistemu.</i> |  CS-STD6 442.50 | 354.00 |  |
|  CDVI Centaur 6 - Enterprise Edition Podržava do 64 sistema, 256 kontrolera*, 2048 vrata* i 16384 kartica*, podržava kontrolisanje liftova, podržava integraciju sa sistemima video nadzora, komunicira sa kontrolerima lokalno (RS-232/RS-485) ili udaljeno (korišćenjem IP modula CA-ETHR-A), aktivira se korišćenjem hardverskog USB ključa, uz softver se isporučuje i jedna workstation licenca CS-WS6 <i>* Broj kontrolera, vrata i kartica je izražen po pojedinačnom sistemu</i> |  CS-ENT6 3863.75 | 3091.00 |  |
|  CDVI Centaur 6 - Workstation Edition Isporučuje se sa jednim USB ključem putem koga se i aktivira |  CS-WS6 331.25 | 265.00 |  |

| Proizvođač | Opis | VP Cena (EUR) | -20% za avansno plaćanje | Foto |
|--|--|-----------------------------|--------------------------|---|
| SISTEMSKI SOFTVER CENTAUR | | | | |
| CDVI | Centaur 5.2 - Standard edition Podržava do 64 sistema, 16 kontrolera*, 128 vrata* i 2048 kartica*. Podržava kontrolisanje liftova. Komunicira sa kontrolerom lokalno (RS-232/RS-485) ili udaljeno (putem modema). Aktivira se korišćenjem serijskog broja i hardverskog ključa. *Po sistemu. Podržava TCP/IP komunikaciju. | CS-AC50-S 442.50 | 354.00 |  |
| &#268;ITA&#269;I | | | | |
| CDVI | Čitač Mifare kartica Horizontalni Mifare bezkontaktni čitač (za spoljnu montažu), radi sa Mifare karticama, polikarbonatsko kućište, LED signalizacija i bazer, do 10 cm domet, 12VDC, 100mA potrošnja | DGLP M WLC 101.25 | 81.00 |  |
| CDVI | DigiProx čitač beskontaktnih kartica, vandal otporan, vertikalni Podržava 26, 30 i 44-bitni Wiegand, direktno vezivanje na CT-V900-A kontroler ili CA-A470-A modul, od nerđajućeg materijala | DGLI F WLC 152.50 | 122.00 |  |
| CDVI | DigiProx čitač beskontaktnih kartica, vandal otporan, horizontalni Podržava 26, 30 i 44-bitni Wiegand, direktno vezivanje na CT-V900-A kontroler ili CA-A470-A modul, od nerđajućeg materijala | DGLI WLC 152.50 | 122.00 |  |
| CDVI | RF prijemnik Podržava 26 i 30-bitni Wiegand, direktno vezivanje na CT-V900-A kontroler ili CA-A470-A modul, od nerđajućeg materijala, mogućnost priključenja antene ANT/433, pokriva do 100m na otvorenom | RECEPTW 155.00 | 124.00 |  |
| CDVI | Beskontaktni čitač kartica Podržava Wiegand 26, 30 ili 44 bit-ne formate, direktna konekcija sa kontrolerom CT-V900-A, audio i vizuelna signalizacija, 12VDC / 100mA, zaštita IP53, belo kućište | STARPW 91.25 | 73.00 |  |
| CDVI | Beskontaktni čitač kartica Podržava Wiegand 26, 30 ili 44 bit-ne formate, direktna konekcija sa kontrolerom CT-V900-A, audio i vizuelna signalizacija, 12VDC / 100mA, zaštita IP53, crno kućište | STARPB 91.25 | 73.00 |  |
| CDVI | Vertikalni beskontaktni čitač (pogodan za spoljnu montažu) Novi dizajn. Više formata očitavanja. Dimenzije 90 x 130 x 35mm, težina 300g. Polikarbonatsko kućište, LED signalizacija i bazer, do 10 cm domet čitanja sa CP (Gloss) karticama, 12VDC, 100mA potrošnja. Dostupan u crnoj (PB) i beloj (PW) boji. | SOLAR PB/PW 91.25 | 73.00 |  |
| SAMOSTALNI &#269;ITA&#269;I | | | | |
| CDVI | Samostalni čitač velikog dometa Podesiv domet do 15m, simultano očitavanje do 20 tagova, memorisanje do 30 korisnika | DTRR1434R 187.50 | 150.00 |  |
| KARTICE | | | | |
| FRADOX | Plavi proximity privezak Proximity privezak velike izdržljivosti, otporan na toplotu sa prorezom za vezivanje. | CR-R704-B 3.50 | 2.80 |  |
| FRADOX | ISO proximity kartica (sjajna) ISO proximity kartica sa veoma dobrom površinom pogodnom za štampanje fotografija. | C706 3.13 | 2.50 |  |

| Proizvođač | Opis | VP Cena (EUR) | -20% za avansno plaćanje | Foto |
|---|--|-----------------------------|--------------------------|---|
| KARTICE | | | | |
|  CDVI | Aktivni tag za čitač DTRR1434 Domet do 15m, u kompletu sa litijumskom baterijom CR2032 | DTXT0434 35.00 | 28.00 |  |
|  CDVI | Beskontaktna mifare kartica ISO 0.8mm | BV 4.50 | 3.60 |  |
| MIFARE PROGRAMATORI | | | | |
|  CDVI | Mifare programator tagova za Cabaprox Kompatibilan sa svim CDVI mifare tagovima, programator otisaka prstiju, upravljanje korisnicima i administratorima, u kompletu sa softverom i USB skenerom | PCMB 734.38 | 587.50 |  |
| BIOMETRIJSKI I MIFARE | | | | |
|  CDVI | Biometrijski i Mifare čitač Neograničen broj korisnika, otisci prstiju se enkriptuju i čuvaju na kartici ili tagu | CABAPROX/W 671.88 | 537.50 |  |
| TASTERI | | | | |
|  CDVI | Taster osetljiv na dodir Od nerđajućeg čelika, može se koristiti kao request-to-exit uređaj, vremenski relej, | BPEST 138.75 | 111.00 |  |