
















































## Katalog opreme za kontrolu pristupa - Geovision - 23.07.2019.



&#268;ITA&#269;I

 <b>Beskontaktni čitač kartica</b> 125kHz ( Proximity EM Card), Wiegand interfejs 26-40bit distanca 30m, podržava RS485 9600bps , 7.5-12Vdc	 <b>GV-Reader 1251</b> 71.73	57.38	
 <b>Beskontaktni čitač kartica Mifare</b> 13.56 MHz (ISO144431 Mifare) ,Wiegand interfejs 26-40bit distanca 30m, podržava RS485 9600bps , 7.5-12Vdc,	 <b>GV-Reader 1352</b> 87.50	70.00	
 <b>Čitač beskontaktnih kartica sa tastaturom</b> GV-Reader 13.56 MHz sa tastaturom , za spoljnu montažu IP66, Wiegand interfejs 26-40bit distanca 30m, podržava RS485 9600bps , 7.5-12Vdc	 <b>GV-RK1352</b> 262.50	210.00	
 <b>Čitač beskontaktnih kartica</b> GV-Reader 13.56 MHz , za spoljnu montažu IP66, Wiegand interfejs 26-40bit distanca 30m, podržava RS485 9600bps , 7.5-12Vdc	 <b>GV-Reader GV-R1352 V100</b> 175.00	140.00	
 <b>Čitač beskontaktnih kartica sa širokougaonom IP kamerom 4MP</b> Širokougaona kamera 4MP, Do 15 fps pri 2048 x 1944, Ugradjen web server, Ugradjeni mikrofoni i zvučnici, GV-AS konekcija kroz Wiegand interfejs, RS-485, 13.56 MHz za ISO14443A (Mifare DESFire, Mifare Plus i Mifare Class) Pristup pomoću kartice i detekcije lica	 <b>GV-CR420 4MP H.264 IP</b> 545.31	436.25	

### KONTROLERI , MODULI

 <b>GV-AS2120 Kontroler</b> Kontroler za 4 vrata / 8 čitača koji podržava 4 Wiegand čitača od 26 do 64 bita. Podržava i GV čitače te GV-GF čitače otiska prsta kroz RS-485 konekciju, max. 8 ukupno. Ugrađeno 8 digitalnih ulaza, 8 relejnih izlaza i ethernet module za spajanje na mrežu i GV-ASManager. Napajanje DC 12V, 3A / PoE+ (IEEE 802.3at). Isporučuje se bez adaptera.	 <b>GV-AS2120</b> 342.19	273.75	
 <b>GV-AS400 kontroler + GV-AS Power Board</b> Podržava 8 Wiegand čitača 26 do 64bits, 40.000 kartica, memoriše do 65.536 događaja-logova,RS485, TCP/IP komunikacija, digitalni I/O 16 ulaza NO/NC, 8 relejni izlaza proširivo do 64 I/O sa GV-IO box, isporučuje se sa napojnom jedinicom za napajanje čiči+10tača, sa izlazom za akumulator, 230Vac	 <b>GV-AS400</b> 998.44	798.75	
 <b>GV-AS120 kontroler sa čitačem</b> Radi na frekvenciji 13.56MHz, 1000/40.000 kartica standalone/mrežni ili RS 485 mod , ima dodatni Wiegand izlaz za jedan čitač, koristi se za jedna vrata; proširiv za druga vrata preko GV ASBox , memoriše 65.536 događaja-logova,digitalni I/O 2 ul/1 izlaz, tamper alarm na pokret, Weather-proof IP66 ,iporučuje se sa softverom GV AS Manager,220Vac	 <b>GV-AS120</b> 262.50	210.00	

Proizvođač	Opis	VP Cena (EUR)	-20% za avansno plaćanje	Foto
<b>KONTROLERI , MODULI</b>				
	<b>GV-ASBox modul</b> I/O modul za GV-AS120, 1 Wiegand interfejs i RS-485 samo za GV-čitače maksimalno 4 čitača, digital I/O 8 ulaza NO/NC, 8 izlaza, 220Vac	 <b>GV-ASBox</b> 389.06	311.25	
	<b>Ekspanzioni mrežni modul za GV-AS100</b> GV-AS110 i GV-AS120.Pomoću GV-ASNet-a GV-AS100, GV-AS110 i GV-AS120 mogu da se povežu sa GV-ASManager-om i da im se pristupi Web interfejsu. Podržava 2 GV čitača	 <b>GV-ASNet</b> 350.00	280.00	
<b>KARTICE, TAGOVI</b>				
	<b>kartica 125kHz za čitače GV Reader 1251</b>	 <b>GV-AS ID card THIN 125kHz</b> 3.99	3.19	
	<b>privezak/tag 125kHz za čitače GV Reader 1251</b>	 <b>GV-AS ID TAG THIN 125kHz</b> 4.69	3.75	
	<b>kartica 13.56MHz, za čitače GV Reader 1352 V2/GV-RK1352/GV-R1352/GV-CR420 i za kontroler GV-AS120</b>	 <b>GV-AS ID card THIN 13.56MHz</b> 3.99	3.19	
	<b>privezak /tag 13.56MHz za čitače GV Reader 1352 V2/GV-RK1352/GV-R1352/GV-CR420 i za kontroler GV-AS120</b>	 <b>GV-AS ID card TAG 13.56MHz</b> 4.69	3.75	
<b>SOFTWARE GV-AS MANAGER</b>				
	<b>Besplatan za 1 do 4 kontrolera GV-AS2120, GV-AS400 ... do 16vrata/ 32 čitača</b>	 <b>GV-AS Manager</b> 0.00	0.00	
	<b>za 1 do 5 kontrolera GV-AS2120, GV-AS400 ... do 20 vrata/ 40 čitača</b>	 <b>GV-AS Manager 55-AS005-000</b> 198.44	158.75	
	<b>za 1 do 6 kontrolera GV-AS2120, GV-AS400 ... do 24 vrata/ 48 čitača</b>	 <b>GV-AS Manager 55-AS006-000</b> 357.81	286.25	
	<b>za 1 do 7 kontrolera GV-AS2120, GV-AS400 ... do 28 vrata/ 56 čitača</b>	 <b>GV-AS Manager 55-AS007-000</b> 517.19	413.75	
	<b>za 1 do 8 kontrolera GV-AS400 ... do 32 vrata/ 64 čitača</b>	 <b>GV-AS Manager 55-AS008-000</b> 676.56	541.25	
	<b>za 1 do 9 kontrolera GV-AS2120, GV-AS400 ... do 36 vrata/ 72 čitača</b>	 <b>GV-AS Manager 55-AS009-000</b> 835.94	668.75	

Proizvođač	Opis	VP Cena (EUR)	-20% za avansno plaćanje	Foto
<b>SOFTWARE GV-AS MANAGER</b>				
	za 1 do 10 kontrolera GV-AS2120, GV-AS400 ... do 40 vrata/ 80 čitača	 <b>GV-AS Manager 55-AS010-000</b> 995.31	796.25	